



## Product Features

- LED indication for timing in progress
- Front protective cover for safety.
- Timer and base available for Track(except H3D1).
- Large transparent knob with lock is provided for precise time setting and protect from unintentional change of time setting.
- **H1DA-X** : Accepts any voltage from 12V AC/DC to 240V AC / 220V DC as signal between command contacts for timing initiation.
- **H1D1-X, H3D1**: Multifunction-On-Delay / Interval / Equal Cyclic-On / Equal Cyclic-Off programmable.

## Specifications

Model	H1DT-10	H1DT-30	H1DT-60	H4DT-10	H4DT-30	H4DT-60
Function	On-Delay					
Rated supply voltage	24V to 240V AC, 24V DC to 220V DC					
Operating voltage range	-10% to +10% of rated voltage					
Rated frequency	50Hz $\pm$ 5%					
Power consumption	AC approx.3VA / 1W, DC approx. 2W					
Allowable ripple (for DC supply)	3% maximum					
Control relay output	2 c/o rated for 5A@250V AC / 28V DC, resistive load					
Time range	1Sec to 10Secs	3Secs to 30Secs	6Secs to 60Secs	1Sec to 10Secs	3Secs to 30Secs	6Secs to 60Secs
Setting accuracy	$\pm$ 10% max. w.r.t full scale $\pm$ 100msec					
Repeat accuracy	$\pm$ 1% max. $\pm$ 100msec					
Recovery time	100msec minimum					
Variation due to voltage change	$\pm$ 2% max $\pm$ 100msec					
Variation due to temp. change	$\pm$ 5% max $\pm$ 100msec					
Variation due to frequency change	$\pm$ 2% max $\pm$ 100msec					
Ambient temperature	Operation: -10°C to +55°C, Storage: -25°C to +80°C					
Humidity	Max. 85% RH @ 40°C					
Service life (under no load)	10 <sup>9</sup> operations minimum					
Electrical life (under full load)	10 <sup>5</sup> operations minimum					
Rated frequency of operation	1800 $\pm$ 5% operations per hour maximum					
Insulation resistance	> 100M ohms @ 500V DC					
Di-electrical strength	1. 1.5KV AC (rms), 50Hz for 1minute. (Between input terminals and enclosure). 2. 1.5KV AC (rms), 50Hz for 1minute. (Between relay contact terminals and enclosure). 3. 1.5KV AC (rms), 50Hz for 1minute. (Between input terminals and relay contact terminals). 4. 1.0KV AC (rms), 50Hz for 10-30sec. Between non-continuous contacts of the relay)			1. 2.5KV AC, 50Hz for 1minute. (Between current carrying and non-current carrying parts). 2. 1.5KV AC, 50Hz for 1minute. (Between contacts and control circuit). 3. 1.0KV AC, 50Hz for 1minute. (Between non-continuous contacts of the relay).		
Electrical connection	11 pin plug-in type			8 pin plug-in type		
Dimension (over-all)	48 x 48 x 94mm (W x H x D)					
Enclosure (series)	H1D series					
Approval	CSA (FILE NO : LR 105610)			N.A		
Panel Cutout	N.A			45mm x 45mm		