

S.No	Model	Specifications	I/P Voltage	Size (in mm) LxWxH	Protection
CONSTANT VOLTAGE MODE					
1	LPH-18-12	O/P 12V, 0~0.15A	180-264V AC / 254-370V DC	140x30x22	IP 67
2	LPH-18-24	O/P 24V, 0~0.75A	180-264V AC / 254-370V DC	140x30x22	IP 67
3	LPV-20-12	O/P 12V, 0~1.67A	90-264V AC / 127-370V DC	118x35x26	IP 67
4	LPV-20-24	O/P 24V, 0~0.84A	90-264V AC / 127-370V DC	118x35x26	IP 67
5	LPV-35-12	O/P 15V, 0~1.5A	90-264V AC / 127-370V DC	148x40x30	IP 67
6	LPV-35-24	O/P 24V, 0~1.5A	90-264V AC / 127-370V DC	148x40x30	IP 67
7	LPV-60-12	O/P 12V, 0~5.0A	90-264V AC / 127-370V DC	162.5x42.5x32	IP 67
8	LPV-60-24	O/P 24V, 0~2.5A	90-264V AC / 127-370V DC	162.5x42.5x32	IP 67
9	LPV-100-12	O/P 12V, 8.5A	90-264V AC / 127-370V DC	190x52x37	IP 67
10	LPV-100-24	O/P 24V, 4.2A	90-264V AC / 127-370V DC	190x52x37	IP 67
CONSTANT CURRENT MODE					
11	APC-12-350	O/P 9~36V, 350mA	90-264V AC / 127-370V DC	77x40x29	—
12	APC-12-700	O/P 9~18V, 700mA	90-264V AC / 127-370V DC	77x40x29	—
13	LPC-20-350	O/P 9~48v, 350mA	90-264V AC / 127-370V DC	118x35x26	IP 67
14	LPC-20-700	O/P 9~30V, 700mA	90-264V AC / 127-370V DC	118x35x26	IP 67
15	LPC-35-700	O/P 9~48V, 700mA	90-264V AC / 127-370V DC	148x40x30	IP 67
16	LPC-35-1050	O/P 9~30V, 1050mA	90-264V AC / 127-370V DC	148x40x30	IP 67
17	LPC-35-1400	O/P 9~24V, 1400mA	90-264V AC / 127-370V DC	148x40x30	IP 67
18	LPC-60-1750	O/P 9~34V, 1750mA	90-264V AC / 127-370V DC	162.5x42.5x32	IP 67
19	LPHC-18-350	O/P 6~48V, 350mA	180-264V AC / 254-370V DC	140x30x22	IP 67
20	LPHC-18-700	O/P 6~25V, 700mA	180-264V AC / 254-370V DC	140x30x22	IP 67
Constant Voltage Mode & Constant Current Mode can be adjusted through internal potentiometer					
21	CLG-100-12	O/P 12V, 0~5.0A	90-295V AC / 127-417V DC	222.2x68x38.8	IP 65
22	CLG-100-24	O/P 24V, 0~4.0A	90-295V AC / 127-417V DC	222.2x68x38.8	IP 65
23	CLG-150-12	O/P 12V, 11A	90-295V AC / 127-417V DC	222.2x68x38.8	IP 65
24	CLG-150-24	O/P 24V, 6.3A	90-295V AC / 127-417V DC	222.2x68x38.8	IP 65
25	HLG-100-24	O/P 24V, 3.2A	90-264V AC / 127-370V DC	220x68x38.8	IP 65
26	HLG-150-24	O/P 24V, 6.3A	90-264V AC / 127-370V DC	228x68x38.8	IP 65
27	HLG-240-24A	O/P 24V, 10A	90-264V AC / 127-370V DC	244.2x68x38.8	IP 65
28	HLG-240H-24A	O/P 24V, 10A	90-305V AC / 127-431V DC	244.2x68x38.8	IP 65
Constant Voltage Mode & Constant Current Mode can be adjusted through internal potentiometer with dimming function					
29	HLG-100-24B	O/P 24V, 4A	90-264V AC / 127-370V DC	220x68x38.8	IP 67
30	HLG-150-24B	O/P 24V, 6.3A	90-264V AC / 127-370V DC	228x68x38.8	IP 67
31	HLG-150H-24B	O/P 24V, 6.3A	90-305V AC / 127-431V DC	228x68x38.8	IP 67
32	HLG-185-24B	O/P 24V, 7.8A	90-264V AC / 127-370V DC	228x68x38.8	IP 67
33	HLG-240-24B	O/P 24V, 10A	90-264V AC / 127-370V DC	244.2x68x38.8	IP 67
34	HLG-240H-24B	O/P 24V, 10A	90-305V AC / 127-431V DC	244.2x68x38.8	IP 67