

| S.No | Model | Specifications | I/P Voltage | Size (in mm) LxWxH | Protection |
|---|--------------|-------------------|---------------------------|-----------------------|------------|
| CONSTANT VOLTAGE MODE | | | | | |
| 1 | LPH-18-12 | O/P 12V, 0~0.15A | 180-264V AC / 254-370V DC | 140x30x22 | IP 67 |
| 2 | LPH-18-24 | O/P 24V, 0~0.75A | 180-264V AC / 254-370V DC | 140x30x22 | IP 67 |
| 3 | LPV-20-12 | O/P 12V, 0~1.67A | 90-264V AC / 127-370V DC | 118x35x26 | IP 67 |
| 4 | LPV-20-24 | O/P 24V, 0~0.84A | 90-264V AC / 127-370V DC | 118x35x26 | IP 67 |
| 5 | LPV-35-12 | O/P 15V, 0~1.5A | 90-264V AC / 127-370V DC | 148x40x30 | IP 67 |
| 6 | LPV-35-24 | O/P 24V, 0~1.5A | 90-264V AC / 127-370V DC | 148x40x30 | IP 67 |
| 7 | LPV-60-12 | O/P 12V, 0~5.0A | 90-264V AC / 127-370V DC | 162.5x42.5x32 | IP 67 |
| 8 | LPV-60-24 | O/P 24V, 0~2.5A | 90-264V AC / 127-370V DC | 162.5x42.5x32 | IP 67 |
| 9 | LPV-100-12 | O/P 12V, 8.5A | 90-264V AC / 127-370V DC | 190x52x37 | IP 67 |
| 10 | LPV-100-24 | O/P 24V, 4.2A | 90-264V AC / 127-370V DC | 190x52x37 | IP 67 |
| CONSTANT CURRENT MODE | | | | | |
| 11 | APC-12-350 | O/P 9~36V, 350mA | 90-264V AC / 127-370V DC | 77x40x29 | — |
| 12 | APC-12-700 | O/P 9~18V, 700mA | 90-264V AC / 127-370V DC | 77x40x29 | — |
| 13 | LPC-20-350 | O/P 9~48v, 350mA | 90-264V AC / 127-370V DC | 118x35x26 | IP 67 |
| 14 | LPC-20-700 | O/P 9~30V, 700mA | 90-264V AC / 127-370V DC | 118x35x26 | IP 67 |
| 15 | LPC-35-700 | O/P 9~48V, 700mA | 90-264V AC / 127-370V DC | 148x40x30 | IP 67 |
| 16 | LPC-35-1050 | O/P 9~30V, 1050mA | 90-264V AC / 127-370V DC | 148x40x30 | IP 67 |
| 17 | LPC-35-1400 | O/P 9~24V, 1400mA | 90-264V AC / 127-370V DC | 148x40x30 | IP 67 |
| 18 | LPC-60-1750 | O/P 9~34V, 1750mA | 90-264V AC / 127-370V DC | 162.5x42.5x32 | IP 67 |
| 19 | LPHC-18-350 | O/P 6~48V, 350mA | 180-264V AC / 254-370V DC | 140x30x22 | IP 67 |
| 20 | LPHC-18-700 | O/P 6~25V, 700mA | 180-264V AC / 254-370V DC | 140x30x22 | IP 67 |
| Constant Voltage Mode & Constant Current Mode can be adjusted through internal potentiometer | | | | | |
| 21 | CLG-100-12 | O/P 12V, 0~5.0A | 90-295V AC / 127-417V DC | 222.2x68x38.8 | IP 65 |
| 22 | CLG-100-24 | O/P 24V, 0~4.0A | 90-295V AC / 127-417V DC | 222.2x68x38.8 | IP 65 |
| 23 | CLG-150-12 | O/P 12V, 11A | 90-295V AC / 127-417V DC | 222.2x68x38.8 | IP 65 |
| 24 | CLG-150-24 | O/P 24V, 6.3A | 90-295V AC / 127-417V DC | 222.2x68x38.8 | IP 65 |
| 25 | HLG-100-24 | O/P 24V, 3.2A | 90-264V AC / 127-370V DC | 220x68x38.8 | IP 65 |
| 26 | HLG-150-24 | O/P 24V, 6.3A | 90-264V AC / 127-370V DC | 228x68x38.8 | IP 65 |
| 27 | HLG-240-24A | O/P 24V, 10A | 90-264V AC / 127-370V DC | 244.2x68x38.8 | IP 65 |
| 28 | HLG-240H-24A | O/P 24V, 10A | 90-305V AC / 127-431V DC | 244.2x68x38.8 | IP 65 |
| Constant Voltage Mode & Constant Current Mode can be adjusted through internal potentiometer with dimming function | | | | | |
| 29 | HLG-100-24B | O/P 24V, 4A | 90-264V AC / 127-370V DC | 220x68x38.8 | IP 67 |
| 30 | HLG-150-24B | O/P 24V, 6.3A | 90-264V AC / 127-370V DC | 228x68x38.8 | IP 67 |
| 31 | HLG-150H-24B | O/P 24V, 6.3A | 90-305V AC / 127-431V DC | 228x68x38.8 | IP 67 |
| 32 | HLG-185-24B | O/P 24V, 7.8A | 90-264V AC / 127-370V DC | 228x68x38.8 | IP 67 |
| 33 | HLG-240-24B | O/P 24V, 10A | 90-264V AC / 127-370V DC | 244.2x68x38.8 | IP 67 |
| 34 | HLG-240H-24B | O/P 24V, 10A | 90-305V AC / 127-431V DC | 244.2x68x38.8 | IP 67 |