

MEANWELL SMPS PRODUCT LIST

S.NO	Model	Watts	Amp.	Dimm (mm) LxWxH	I/P Voltage
24 VOLTS DC – MODELS / SUPER COMPACT NES / RS SERIES					
1	RS-15-24	15	0.625	62.5x51x28	85-264V AC / 120-370V DC
2	NES-25-24	25	1.1	99x82x35	85-264VAC/120-370V DC
3	RS-25-24	25	1.1	78x51x28	88-264VAC/125-373V DC
4	RS-35-24	35	1.5	99x82x36	88-264VAC/125-373V DC
5	LRS-35-24	35	1.5	99x82x30	85-264VAC/120-373V DC
6	RS-50-24	50	2.2	99x97x36	88-264VAC/125-373V DC
7	LRS-50-24	50	2.2	99x82x30	85-264VAC/120-373V DC
8	S-60-24	60	2.5	159x97x38	85-264VAC/120-370V DC
9	LRS-75-24	75	3.2	99x97x30	85-264V AC / 120-373VDC
10	NES-100-24	100	4.5	159x97x38	85-132VAC/248-373V DC
11	SP-100-24	100	4.2	179x99x45	85-264VAC/120-370V DC
12	SE-100-24	100	4.5	159x97x38	85-132VAC/248-373V DC
13	RS-100-24**	100	4.5	159x97x38	88-264VAC/125-373V DC
14	LRS-100-24	100	4.5	129x97x30	85-264VAC/120-373V DC
15	SP-150-24	150	6.3	199x99x50	85-264VAC/120-370V DC
16	RS-150-24	150	6.5	199x98x38	88-132VAC/248-373V DC
17	LRS-150-24	150	6.5	159x97x30	85-132VAC/240-370V DC
18	LRS-150F-24	150	6.5	159x97x30	85-264VAC/120-373V DC
19	SE-200-24	200	8.8	215x115x50	90-132 / 180-264 V AC
20	SP-200-24	200	8.4	199x99x50	85-264VAC/120-370V DC
21	LRS-200-24	200	8.8	215x115x30	90-132/ 180-264 V AC
22	S-250-24	250	10	150x140x86	90-132 / 176-264 V AC
23	NES-350-24	350	14.6	215x115x50	90-132 / 180-264 V AC
24	LRS-350-24	350	14.6	215x115x30	90-132 / 180-264 V AC
25	SP-240-24	240	10	190x93x50	88-264V AC / 124-370V DC
26	SP-320-24	320	13	215x115x50	88-264V AC / 124-370V DC
27	RSP-500-24	500	21	230x127x40.5	85-264V AC / 120-370V DC
28	SE-450-24	450	18.8	225x124x50	90-132V AC / 180-264 V AC
29	MSP-450-24	450	18.8	218x105x41	85-264V AC / 120-370V DC
30	SE-600-24	600	25	247x127x63.5	90-132 / 180-264V AC
31	PSP-600-24	600	25	170x120x93	88-264V AC / 124-370V DC
32	SP-750-24	750	31.3	278x127x63.5	90-264V AC / 127-370V DC
33	SE-1000-24	1000	41.7	278x127x63.5	90-132 / 180-264V AC
34	SE-1500-24	1500	62.5	278x177.8x63.5	180-264V AC/254-370V DC
35	RSP-1000-24	1000	40	295x127x41	91-264V AC / 127-370V DC
36	RSP-2000-24	2000	80	295x127x41	91-264V AC / 127-370V DC
37	RSP-2400-24	2400	100	278x177.8x63.5	180-264V AC/254-370V DC
12 VOLTS DC OUTPUT – MODELS / SUPER COMPACT NES SERIES					
1	RS-15-12	15	1.3	62.5x51x28	85-264VAC / 120-370ADC
2	RS-25-12	25	2.1	78x51x28	88-264VAC / 125-373VDC
3	RS-35-12	35	3	99x82x36	88-264VAC / 125-373VDC
4	LRS-35-12	35	3	99x82x30	85-264VAC/125-373V DC

S.NO	Model	Watts	Amp.	Dimm (mm) LxWxH	I/P Voltage
5	RS-50-12	50	4.2	99x97x36	88-264VAC / 125-373VDC
6	LRS-50-12	50	4.2	99x82x30	85-264VAC/120-373V DC
7	LRS-75-12	75	6	99X97X30	85-264V AC / 120-373VDC
8	SE-100-12	100	8.5	159x97x38	85-132V AC /176-264V AC
9	LRS-100-12	100	8.5	129x97x30	85-264VAC/120-373V DC
10	RS-150-12	150	12.5	199x98x38	88-132VAC / 248-373V DC
11	LRS-150-12	150	12.5	159x97x30	85-132VAC/240-370V DC
12	LRS-150F-12	150	12.5	159x97x30	85-264VAC/120-373V DC
13	RPS-160-12	161	12.9	127x76.2x34.6	90-264V AC / 127-370VDC
14	SE-200-12	201	16.8	215x115x50	92-132VAC / 180-264V AC
15	LRS-200-12	200	17	215x115x30	90-132V AC / 180-264 V AC
16	S-250-12	250	18	150x140x86	90-132VAC / 176-264VAC
17	S-240-12	240	18	190x93x65	88-132VAC / 176-264V DC
18	SP-240-12	240	20	190x93x50	88-264V AC / 124-370V DC
19	SP-320-12	320	25	215x115x50	88-264V AC / 124-370V DC
20	SE-350-12	350	29	215x115x50	90-132V AC / 180-264V AC
21	LRS-350-12	350	29	215x115x30	90-132V AC / 180-264V AC
22	NES-350-12	350	29	215x115x50	90-132V AC / 180-264 V AC
23	SE-450-12	450	37.5	225x124x50	90-132V AC / 180-264 V AC
24	SP-500-12	500	40	170x120x93	88-264V AC / 124-370V DC
25	SE-600-12	600	50	247x127x63.5	90-132VAC / 180-264VAC
26	SP-750-12	750	62.5	278x127x63.5	90-264V AC / 127-370VDC
27	SE-1000-12	1000	83.3	278x127x63.5	90-132VAC / 180-264VAC
28	SE-1500-12	1500	125	278x177.8x63.5	180-264V AC / 254-370V DC
29	RPSG-160-12	161	12.9	127x76.2x34.6	90-264V AC / 127-370VDC
15 VOLTS DC OUTPUT – MODELS / SUPER COMPACT NES SERIES					
1	RS-15-15	15	1	62.5x51x28	85-264V AC / 120-370V DC
2	RS-25-15	25	1.7	78x51x28	88-264VAC / 125-373VDC
3	NES-35-15	35	2.4	99x97x36	85-264V AC / 120-370V DC
4	LRS-35-15	35	2.4	99x82x30	85-264VAC/125-373V DC
5	RS-50-15	50	3.4	99x97x36	88-264V AC / 125-373V DC
6	NES-50-15	50	3.4	129x98x38	85-264V AC / 120-370V DC
7	LRS-50-15	50	3.4	99x82x30	85-264VAC/120-373V DC
8	LRS-75-15	75	5	99X97X30	85-264V AC / 120-373VDC
9	NES-100-15	100	7	159x97x38	85-132V AC / 176-264V AC
10	LRS-100-15	100	7	129x97x30	85-264VAC/120-373V DC
11	RS-150-15	150	10	199X98X38	88-132VAC / 248-373V DC
12	LRS-150-15	150	10	159x97x30	85-132VAC/240-370V DC
13	S-201-15	200	13	215x115x50	90-132V AC / 180-264VAC
14	S-250-15	250	15	150x140x86	90-132V AC / 176-264V AC
15	LRS-350-15	350	23.2	215x115x30	90-132V AC / 180-264V AC
16	NES-350-15	350	23.2	215x115x50	90-132V AC / 180-264 V AC
17	SE-450-15	450	30	225x124x50	90-132V AC / 180-264 V AC
18	SP-500-15	500	32	170x120x93	88 - 264V AC / 124-370VDC
19	SE-600-15	600	40	247x127x63.5	90-132V AC / 180-264V AC

S.NO	Model	Watts	Amp.	Dimm (mm) LxWxH	I/P Voltage
20	SE-1000-15	1000	66.7	278x127x63.5	90-132V AC / 180-264V AC
21	SE-1500-15	1500	100	278x177.8x63.5	180-264VAC / 254-370V DC
5 VOLTS MODELS / SUPER COMPACT NES SERIES					
1	RS-25-3.3	25	6	78x51x28	88-264VAC / 125-373VDC
2	RS-15-5	15	3	62.5x51x28	85-264V AC / 120-370V DC
3	RS-25-5	25	5	78x51x28	88-264VAC / 125-373VDC
4	RS-35-5	35	7	99x82x36	88-264VAC / 125-373VDC
5	LRS-35-5	35	7	99x82x30	85-264VAC/125-373V DC
6	NES-50-5	50	10	129x98x38	85-264V AC / 120-370V DC
7	RS-50-5	50	10	99x97x36	88-264VAC / 125-373VDC
8	LRS-50-5	50	10	99x82x30	85-264VAC/120-373V DC
9	S-60-5	60	12	159x97x38	85-264V AC / 120-370V DC
10	LRS-75-5	75	14	99x97x30	85-264V AC / 120-373VDC
11	RS-100-5	100	16	159x97x38	88-264VAC / 125-373VDC
12	SE-100-5	100	20	159x97x38	85-132V AC / 176-264V AC
13	LRS-100-5	100	18	129x97x30	85-264V AC /120-373V DC
14	RS-150-5	150	26	199x98x38	88-132VAC / 248-373V DC
15	LRS-150F-5	150	22	159x97x30	85-264VAC/120-373V DC
16	LRS-200-5	200	40	215x115x30	90-132V AC / 180-264 V AC
17	S-250-5	250	40	150x140x86	90-132V AC / 176-264V AC
18	NES-350-5	350	60	215x115x50	90-132V AC / 180-264V AC
19	LRS-350-5	350	60	215x115x30	90-132V AC / 180-264V AC
20	SE-600-5	600	100	247x127x63.5	90-132V AC / 180-264V AC
21	SE-1000-5	1000	150	278x127x63.5	90-132V AC / 180-264V AC
22	SE-1500-5	1500	300	278x177.8x63.5	180-264V AC / 254-370V DC
36 VOLTS MODELS / SUPER COMPACT NES SERIES					
1	LRS-150-36	150		199x98x38	88-132VAC / 248-373V DC
2	NES-350-36	350	9.7	215x115x50	90-132V AC / 180-264V AC
3	SE-600-36	600	16.6	247x127x63.5	90-132V AC / 180-264V AC
48 VOLTS MODELS					
1	RS-50-48	50	1.1	99x97x36	88-264VAC / 125-373VDC
2	LRS-50-48	50	4.2	99x82x30	85-264VAC/120-373V DC
3	SE-100-48	100	2.3	159x97x38	85-132V AC / 176-264V AC
4	LRS-100-48	100		129x97x30	85-264V AC /120-373V DC
5	RS-150-48	150	3.3	199x98x38	88-132VAC / 248-373V DC
6	LRS-150-48	150	3.3	159x97x30	85-132VAC/240-370V DC
7	LRS-200-48	200	4.4	215x115x30	90-132V AC / 180-264 V AC
8	SP-240-48	240	5	190x93x50	88-264VAC / 124-370VDC
9	S-250-48	250	5.2	150x140x86	90-132V AC / 176-264V AC
10	NES-350-48	350	7.3	215x115x50	90-132V AC / 180-264V AC
11	LRS-350-48	350	7.3	215x115x30	90-132V AC / 180-264V AC
12	SE-450-48	450	9.4	225x124x50	90-132V AC / 180-264 V AC
13	SP-480-48	480	10	225x124x51	85-264V AC / 120-370V DC

S.NO	Model	Watts	Amp.	Dimm (mm) LxWxH	I/P Voltage
14	SP-500-48	500	10	170x120x93	88 - 264V AC / 124-370V DC
15	SE-600-48	600	12.5	247x127x63.5	90-132V AC / 180-264V AC
16	SE-1000-48	1000	20.8	278x127x63.5	90-132V AC / 180-264V AC
17	SE-1500-48	1500	31.3	278x177.8x63.5	180-264V AC / 254-370V DC
18	RSP-1000-48	21	21	295x127x41	90-264VAC/127-370VDC
19	RSP-2000-48	2000	42	295x127x41	90-264VAC/127-370VDC
20	RSP-2400-48	2400	50	278x177.8x63.5	180-264V AC/254-370V DC
21	RSP-500-48	500	10.5	230x127x40.5	85-264V AC/120-370V DC
DIN RAIL MOUNTED MODELS					
MINIATURE					
1	EDR-75-12	75	6.3	32x125.2x102	90-264V AC / 127-370V DC
2	EDR-75-24	75	3.2	32x125.2x102	90-264V AC / 127-370V DC
3	EDR-120-12	120	10	40x125.2x113.5	90-264V AC / 127-370V DC
4	EDR-120-24	120	5	40x125.2x113.5	90-264V AC / 127-370V DC
5	EDR-120-48	120	2.5	40x125.2x113.5	90-264V AC / 127-370V DC
6	EDR-150-24	150	6.5	40x125.2x113.5	90-264V AC / 127-370V DC
7	HDR-15-24	15	0.63	17.5x90x54.5	85-264V AC/ 120-370V DC
8	HDR-30-24	30	1.5	35x90x54.5	85-264V AC/ 120-370V DC
9	MDR-10-24	10	0.42	22.5x90x100	85-264V AC/ 120-370V DC
10	MDR-20-24	20	1	22.5x90x100	85-264V AC/ 120-370V DC
11	MDR-40-24	40	1.7	100x90x40	85-264V AC/ 120-370V DC
12	MDR-60-12	60	5	40x90x100	85-264vac/120-370V DC
13	MDR-60-24	60	2.5	40x90x100	85-264V AC/ 120-370V DC
14	MDR-100-24	100	4	50x90x100	85-264V AC/ 120-370V DC
DIN RAIL MOUNTED MODELS					
1	NDR-240-24	240	10	63x125.2x113.5	90-264V AC/ 127-370V DC
2	NDR-240-48	240	5	63x125.2x113.5	90-264V AC/ 127-370V DC
3	NDR-480-24	480	20	85.5x125.2x128.5	90-264V AC/ 127-370V DC
4	NDR-480-48	480	10	85.5x125.2x128.5	90-264V AC/ 127-370V DC
REGULAR					
1	DR-30-12	30	2	78x93x56	85-264V AC/ 120-370V DC
2	DR-30-24	30	1.5	78x93x56	85-264V AC/ 120-370V DC
3	DR-45-05	45	5	93x78x67(LWH)	85-264V AC/ 120-370V DC
4	DR-45-12	45	3.5	93x78x67(LWH)	85-264V AC/ 120-370V DC
5	DR-45-15	45	2.8	93x78x67(LWH)	85-264V AC/ 120-370V DC
6	DR-45-24	45	2	93x78x67(LWH)	85-264V AC/ 120-370V DC
7	DR-60-12	60	4.5	78x93x56	88-264VAC / 124-370VDC
8	DR-60-24	60	2.5	78x93x56	88-264vaC / 124-370VDC
9	DR-75-24	75	3.2	55.5x125.2x100	85-264V AC/ 120-370V DC
10	DR-100-12	100	7.5	100x93x56	88-264VAC / 124-370VDC
11	DR-120-12	120	10	65.5x125.2x100	88-132VAC / 176-264V AC

S.NO	Model	Watts	Amp.	Dimm (mm) LxWxH	I/P Voltage
12	DRH-120-24	120	5	65.5x125.2x100	340-550VAC / 480-780V DC
13	DRP-240-24	240	10	125.5x125.2x100	85-264V AC/ 120-370V DC
14	DRP-240-48	240	5	125.5x125.2x100	85-264V AC/ 120-370V DC
15	DRP-480S-24	480	20	227x125.2x100	90-132VAC/180-264VAC
16	DRP-480S-48	480	10	227x125.5x100	90-132VAC/180-264VAC
17	DRP-480-24	480	20	227x125.2x100	180 - 264V AC/ 250-370V DC
18	DRP-480-48	480	10	227x125.2x100	180-264V AC/ 250-370V DC
19	SDR-960-24	960	40	110x125.2x150	180-264V AC / 254-370V DC
20	WDR-240-24	240	10	63x125.2x113.5	180-550V AC / 254-754V DC
21	WDR-480-24	480	20	85.5x125.2x128.5	180-550V AC / 254-754V DC
DIN RAIL THREE PHASE SERIES (3 phase input but 2 phase operation also possible)					
1	DRT-240-24	240	10	125.5x125.2x100	340-550V AC / 3 Phase
2	DRT-480-24	480	20	227x125.2x100	340-550V AC / 3 Phase
3	DRT-480-48	480	10	227x125.2x100	340-550V AC / 3 Phase
4	DRT-960-24	960	40	276x125.2x100	340-550V AC / 3 Phase
5	DRT-960-48	960	20	276x125.2x100	340-550V AC / 3 Phase
6	TDR-480-24	480	20	85.5x125.2x128.5	340-550V AC / 3 Phase
7	TDR-960-24	960	40	110x125.2x150	340-550V AC / 3 Phase
DUAL, TRIPLE & FOUR OUTPUT MODELS				Dimm (mm) LxWxH	
1	RD-35A	35	+5V / 4A	99x82x36	88-264V AC /
			+12V / 1A		125-373V DC
2	NED-35B	35	+5V / 2.2A	99x97x36	85-264V AC /
			+24V / 1A		120-370V DC
	RD-35B	35	5V / 2.2 A	99x82x36	85-264V AC /
			24V / 1 A		125-3730V DC
3	NED-100D	100	+24V / 3.5A	199x98x38	88-132V AC /176 - 264V AC
			+5V / 3A		248-373V DC
4	D-60A	60	+5V / 4A	159x97x38	85-264V AC /
			+12V / 3A		120-370V DC
5	RD-65A	66	5V / 6A	129x98x38	88-264V AC
			12V / 3A		125-373V DC
6	RD-50A	50	+ 5 V / 6A	99x97x36	88-264V AC
			12 V / 2A		125-373V DC
7	NED-75A	75	+ 5V / 7A	159x97x38	85-264V AC /
			12 V / 3 A		120-370V DC
8	D-60B	60	+5V / 3A	159x97x38	85-264V AC/
			+24V / 1.8A		120-370V DC
9	RD-65B	68	5V / 4A	129x98x38	88-264V AC
			+24V / 2A		125-373V DC
10	NED-75B	75	+ 5 V / 5 A	159x97x38	85-264V AC /
			24V/ 2 A		120-370V DC
11	RD-85A		5 V / 8A	159x97x38	88 - 264VAC / 125 - 373VDC

S.NO	Model	Watts	Amp.	Dimm (mm) LxWxH	I/P Voltage
			12 V / 4 A		
12	D-120A	120	+5V / 12A	199x110x50	88-132VAC/176-264V AC
			+12V / 5A		284 - 370V DC
13	D-120B	120	+5V / 6A	199x110x50	88-132VAC/176-264VAC
			+24 V / 4A		284 - 370V DC
14	RD-125B	133.4	5V / 4.6A	199x98x38	88-132VAC/'176-264VAC
			24V / 4.6A		248-373V DC
15	T-30B	30	+5V / 3A	129x98x38	85-132VAC / 170-264VAC
			+12V / 1A		240-370V DC
			-12V / 0.5A		
16	T-40A	40	+5V / 3A	129x98x38	85-264V AC /
			+12V / 2A		120-370V DC/ 240-370V DC
			- 5V / 0.5A		
17	T-40B	40	+5V / 3A	129x98x38	85-264V AC /
			+12V / 2A		120-370V DC/ 240-370V DC
			-12V / 0.5A		
18	T-60A	60	+5V / 5A	159x97x38	85-264V AC /
			+12V / 2.5A		120-370V DC
			-5V / 0.5A		
19	NET-75A	75	5 V / 6 A	159x97x38	85-264V AC /
			12 V / 3 A		120-370V DC
			- 5 V / 0.5 A		
20	RT-50B	50	+5V / 4A	99x97x36	85-264V AC /
			+12V / 2A		125-373V DC
			-12V / 0.5A		
21	T-60B	60	+5V / 5A	159x97x38	85-264V AC /
			+12V / 2.5A		120-370V DC
			-12V / 0.5A		
22	RT-65B	64.6	+5V / 5A	129x98x38	88-264V AC
			+12V / 2.8A		125-373V DC
			-12V / 0.5A		
23	NET-75B	75	5 V / 5 A	159x97x38	85-264V AC /
			12 V / 2.8 A		120-370V DC
			-12 V / 0.5 A		
24	T-60C	60	+5V / 5A	159x97x38	85-264V AC /
			+15V / 2A		120-370V DC
			-15V / 0.5A		
25	RT-65C	65	+5V / 5A	129x98x38	88-264V AC
			15V / 2.2 A		125-373V DC
			-15V / 0.5A		
26	NET-75C	75	5 V / 6 A	159x97x38	85-264V AC /
			15 V / 2.3 A		120-370V DC
			- 15 V / 0.5 A		
27	T-120B	120	+5V / 11A	199x110x50	88 - 132VAC/176-264V DC
			+12 V / 4.5A		240 - 370VDC
			-12V / 1A		

S.NO	Model	Watts	Amp.	Dimm (mm) LxWxH	I/P Voltage
28	T-120C	120	+5V / 10A	199x110x50	88 - 132VAC/176-264V DC
			+15 V / 3.5A		240 - 370VDC
			-15V / 1A		
29	RT-125C		+5V / 10A	199x98x38	88 - 132VAC/176-264V DC
			+15 V / 4.5A		248 - 373VDC
			-15V / 1A		
30	Q-60B	60	+5V / 5.5A	159x97x38	85-264V AC /
			+12V / 2A		120-370V DC
			-5V / 0.5A		
			-12V / 0.5A		
31	RQ-65B	62.5	+5V / 6A	129x98x38	88-264V AC
			+12V / 2A		125-373V DC
			-5V / 0.5A		
			-12V / 0.5A		
32	Q-120B	120	+5V / 11A	199x110x50	88-132VAC/176-264V AC
			+12V / 4A		240-370V DC
			-5V / 1A		
			-12V / 1A		
33	RQ-125B	120	+5V / 11A	199x110x50	88-132VAC/176-264V AC
			+12V / 4.5A		240-370V DC
			-5V / 1A		
			-12V / 0.5A		
34	Q-120C	120	+5V / 10A	199x110x50	88-132VAC/176-264V AC
			+15V / 3.5A		240-370V DC
			-5V / 1A		
			-15V / 1A		
35	Q-60D	60	+5V / 4A	159x97x38	85-264V AC /
			+12V / 1A		120-370V DC
			+24V / 1A		
			-12V / 0.5A		
36	RQ-65D	62.5	+5V / 4 A	129x98x38	88-264V AC
			+12V / 1.5A		125-373V DC
			-24V / 1 A		
			-12V / 0.5 A		
37	Q-120D	120	+5V / 8A	199x110x50	88-132VAC/176-264V AC
			+12V / 2A		240-370V DC
			+24V / 2A		
			-12V / 1A		
38	RQ-125D		+5V / 8A	199x98x38	88-132VAC/176-264V AC
			+12V / 2.5A		248-373V DC
			+24V / 2A		
			-12V / 0.5A		
39	Q-250D	250	+5V / 10A	150x140x86	90-132VAC/176-264V AC
			+12V / 5A		248-370V DC
			+24V / 5A		
			-12V / 1A		

S.NO	Model	Watts	Amp.	Dimm (mm) LxWxH	I/P Voltage
40	PT-65D		5 V / 4A	127x76x42	90- 264V AC / 127-370VDC
			12 V / 2 A		
			24 V / 1A		
OPEN FRAME PCB TYPE SWITCHING POWER SUPPLY					
1	EPS-15-5	15	3	63.5x45.7x24	85-264V AC/ 120-370C DC
2	EPS-15-12	15	1.25	63.5x45.7x24	85-264V AC/ 120-370C DC
3	EPS-25-5	25	5	76.2x50.8x24	85-264V AC/ 120-370C DC
4	EPS-25-12	25	2.1	76.2x50.8x24	85-264V AC/ 120-370C DC