

Electronic Hooter



Features

- Tone Reset facility can be given on specific demand.
- Solid state design using integrated circuitry.

Technical Specifications & Features

- Supply Voltage : 12, 24, 48, 110, 230, 415 V AC
 $\pm 15\%$, 50Hz.
12, 24, 30, 48, 110, 220 VDC $\pm 15\%$
- Tones : Continuous and Intermittent (Both can be given in single unit – selection by means of link provided on backside terminal strip.
- Volume Control : Continuous adjustable by means of Potentiometer (optional features)
- Cut-out Dimensions : 92 x 92 mm
- Overall Dimensions : 96 x 96 x 150 mm

Application Areas

Thermal power stations and sub-stations of Electricity Boards, Steel Plants, Sugar Industries, Cement and Chemical Industries, A.C. Plants, Process Plants, Heat Treatment Plants, Hotels, Fire Alarm Systems and in telephone exchanges as Audio – Visual Panels etc.



DIGITAL PROMOTERS
(INDIA) PRIVATE LIMITED

502 & 505, Vishal Bhawan, 95 Nehru Place, New Delhi-110 019, INDIA
Ph : 41618100 (3 Lines), 011-26418118 Fax : 26437849
Email : digitalpromoters@gmail.com • info@digitalpromoters.com
Website : www.DigitalPromoters.com

